

MED85R (Single Swing Glass Door Medical Fridge with Low - E Glass)

ISO 9001	YES
IEC 60335 Compliant	YES

Specifications

Manufacturers Gross Volume (L)	Refrigerator 75L
Adjustable Shelves	4 (Stainless Steel)
Inner Body Material	Aluminium
Exterior Body Material	Stainless Steel & White Coated Mild Steel (Chromadek)
Fridge Temperature Display	YES
Temperature (Fridge)	+2°C To +8°C At +35°C Ambient
Accurate Temperature Control	YES (0.1°C Accuracy)
Interior Light - LED	YES (Auto Off After 10 Min Of Operating Door)
Visible Digital Temperature Control	YES
Internal Compartment Fan	YES
Door Locking System	YES
Glass Doors	1 – Double Glazed With UV Protection (Low-E)
Automatic Defrost	YES
High / Low Temperature Alarm +2°C to +8°C	YES (Audible & Visual & Will Sound If Temperature Out Of Set Parameters For More Than 5 Minutes)
Door Open Alarm	YES (Audible Alarm Will Sound After 60 Seconds When The Door Has Been Left Open)
Battery Alarm For Power Outage	YES (Audible & Visual With >48Hrs Capacity)
Insulation	Ecomate Polyurethane (Zero GWP & Zero ODP)
Door Open Alarm	YES (Visual After 60 Seconds)
CFC & HCFC Free	YES
Mains Cable Length With Plug	3.1M
Adjustable Feet	Optional
Swivel Castors	YES - 4 (2 Lockable)
Voltage Stabiliser	YES (Combined Surge Protect & Voltage Stabiliser)
RTMD Ready	YES
Interior Light Manual Switch	YES (External)



Performance Information

Hold Over Time During Power Cut	>48 Hours
---------------------------------	-----------

Dimensions

External Without Castors	(H) 1028mm x (W) 619mm x (D) 563mm
External With Castors	(H) 1128mm x (W) 619mm x (D) 563mm
Weight (Kg's) - Boxed	65



Supplied By Zero Appliances (Pty) Ltd • Johannesburg, South Africa

☎ 010 207 1600 • 📠 010 207 1675 •

✉ albert@zeromedical.co.za • 🌐 www.zeroappliances.co.za

E&OE Errors and Omissions Excepted